SUNKOLL TILES CLEANER Technical Data Sheet



SUNKOLL TILES CLEANER is a high quality rapid active cleaner and degreasing solution for use on tiles, bathtubs, wash basin, privy basin and concrete etc. It is used to clean whitish spot/ layer as normally observed in the bathroom under plastic/ metal buckets (normal detergent is not helpful) with ease. It is also used as rapid removal of white yellowish spot/layer along with water stains over tiles, cement stains, grime, oil, paint stains, grease, moss and wax from concrete, asbestos, terrazzo and ceramics.

How To Us





FEATURES AND ADVANTAGES SUNKOLL TILES CLEANE

- Easy to use just mix with water & clean the surface.
- Removes difficult stains easily Fast & effective.
- Degreases the tile surface easily for soaps, scum, efflorescence, mineral deposit.
- Cleans all types of tile like ceramic, porcelain & vitrified tile and grout.
- Protects the color & shine of tile.
- Does not damage joints between ceramic tiles, even those grouted with colored products.
- Not harmful like acid.

SUNKOLL TILES CLEANER



Application Area

- Material to be Cleaned: For removing mild spots on tiling surfaces such as toilet floors and walls, kitchen areas, and other tiling or ceramic surfaces, a 1:1 proportion of SUNKOLL TILES CLEANER is recommended.
- Area of Application: Use a clean cloth and dip in the degreasing diluted solution and gently rub the tiling surface. Repeat the process till you get the desired results.
- It is recommended to use a non-diluted (neat) solution/liquid of SUNKOLL TILES CLEANER to get rid of stubborn stains/layers on the surface. It is recommended to patch test on a small section before using the liquid on the entire area.
- For everyday use, use two caps of SUNKOLL TILES CLEANER liquid with half a bucket of water. It is perfect for mopping the tiled areas of the house.

TECHNICAL INFORMATION

Testing Properties Density	Test Results 1.02 ± 0.02 kg/ litre
Color	Reddish Liquid
Viscosity	Equal to water
Soaking Time	5 minutes
Dilution with Water	Dilution with water will depend upon substrate condition & Stain severity.





नए भारत क नई ताकत

Technical Performances

Density	1.02 ± 0.02 kg/ litre
Color	Reddish Liquid
Viscosity	Equal to water
Soaking Time	5 minutes
Dilutionwith Water	Dilution with water will depend upon substrate condition & Stain severity.

Important Instructions :

- Keep out of reach of children. Wear suitable protective clothing, gloves and eyes/face protection.
- After contact with skin, wash immediately with plenty of clean water.
- In case of contact with eyes rinse immediately with plenty of clean water and seek medical advice.
- Limited to professional use only. For more details please refer the relevant Material Safety Data Sheet, available on request.

SUNKOLL TILES CLEANER





SUNKOLL Green Building Index :

SUNKOLL Range of Products are most eco-friendly and suitable to use in all kind of buildings including certi ied green. Apart from using best of international raw material for best performance, SUNKOLL procure the major raw material locally to safeguard environment.

SUNKOLL Quality & Safety Assurance

Products supplied are safe to use by any worker at site. However proper tools and safety measures must be in place for prolong working. The gloves, safety glasses and other protection measure must be followed as per local regulation.

Declaration :

Check before using the product about performance and inal expected results. **SUNKOLL** cannot be held All the above information and results are provided based on **SUNKOLL** internal quality test. Customer must responsible for any damage of whatsoever nature at site.

UNIT - 1 SUNKOLL INDUSTRIES LIMITED

Plot No. 62, Tarang Industial Estate Hadamtada Ta. Kotda Sangani N.H. 8-B Rajkot(Gujarat) - 360 311

- UNIT 2 SUNKOLL INDUSTRIES LIMITED BARODA
- UNIT 3 SUNKOLL INDUSTRIES LIMITED JAIPUR
- UNIT 4 SUNKOLL INDUSTRIES LIMITED GUWAHATI

TECHNICAL SERVICES & CUSTOMER CARE MANAGER : +91 70698 82251

TOLL FREE : 1800 890 2343

Email: sunkollindltd@gmail.com